



999.00 EUR
incl. 19% VAT, plus [shipping](#)

- Fanless !
- 512 MB RAM !
- 1.2 Ghz !
- Compact Flash



Support: [HDD-Installation \[DE\]](#) | [HDD-Installation \[EN\]](#) | [Drivers \(Win\)](#) | [Graphics Driver \(Win\)](#)

Fanless PC-Barebone. For a full-featured PC you only need to add one 2.5" PATA harddrive.

Because of its size (170 x 123 x 56 mm !) the system is perfect for these applications :

- POS
- Digital Signage
- Kiosk

Or use as attractive office-computer or server.

FBox-CF : Like FBox, but has 1x Bootable Compact Flash reader instead of 2x RS232

| | |
|----------------|--|
| CPU | VIA Eden Esther 1.2GHz processor |
| BIOS | AMI BIOS |
| System Chipset | VIA CX700M |
| I/O Chip | VT1211 |
| System Memory | Onboard 512MB DDR2 |
| MIO | 1xEIDE(UltraDMA 133),1x PS/2 K/B,1x P/S2 Mouse |
| PRT | 1x Printer port |
| Compact-Flash | 1x Bootable Compact-Flash Reader |

| | |
|-------------------------------------|---|
| USB | 2 X USB 2.0 Ports (one at front) |
| Output | VGA |
| Display Chipset | Integrated VIA UniChrome Pro II,2D/3D Graphics with MPEG4 and WMV9 decoding accelerator |
| Display Memory | Up to 128MB share system memory |
| Display Resolution | Up to 1920 x 1440 |
| Audio AC97 2.2(Codec) | VIA Vinyl VT1708 |
| Audio Interface | Line Out, Mic In |
| Ethernet Chipset | Realtek RTL8100B 10/100 Base-T Ethernet |
| Ethernet Remote Boot ROM | built-in boot ROM function (PXE Supported) |
| 2.5" Hard Disk installation support | YES |
| Power Requirement | +5V@4A |
| Operating Temp | 0 ~ 60°C (32-140 °F) |
| Operating Humidity | 0% - 90% relative humidity, non-condensing |
| Size (W x H x D) | 170 x 123 x 56 mm |
| Weight | 970g |
| Certification | CE,FCC |